



## Dual Leslie Pro-Audio Driver Kit

### Installation

1. Remove center & lower section back panels of the Leslie.
2. Unplug the green & black wire from the crossover.
3. Remove the upper driver. It is held in with 3 10/24 screws. Save the round spacer for future use.
4. Once the treble driver is removed, go back and check the plastic horn to see if there is a wad of cotton inside, if there is remove wad of cotton from the spinning section of the horn.
5. Remove the black & green wires from the old driver.
6. Remove the upper driver bearing plate assembly. At this point you should clean and degrease this item.
7. Remove the old Jensen driver from the gray mounting plate. Using the four screw holes that were holding the old driver, mount the new driver adaptor Mount using the screws provided.
8. Reinstall the old plate with the new mount & bearing assembly. Make note use the round spacer just as it came off the old driver.
9. Screw the new treble drivers onto the installed plate.
10. Install the GREEN/BLACK wire harness on to the new Peavey drivers.

*Note: You will put the black on the - of the 1st driver. Connect the yellow jumper from the + of driver #1 to the minus of driver #2. The green goes to the + of driver #2. The connection is in series.*

11. Install the tone cabinet backs, being sure to tighten all screws (If any screws are missing, replace them!).
12. Have Fun & cover your ears!!

Speakeasy Vintage Music  
3250 Schoolhouse Road  
Dover, PA 17315  
Ph: (717) 292-0814  
Web: <http://www.speakeasyvintagemusic.com>